CDPA-18X16-147AHD IR PTZ Dome Camera





- Salation for 720p resolutions over coax
- IP66 rated weatherproof housing
- DWDR technology for great performance in all lighting
- True day/night performance, utilizing a motorized IR cut filter
- Built-in surge protection (transient 6000V)
- 0 lux with IR LEDs on
- High intensity IR array with smart IR LED control for IR projection up to 492 feet
- 18X optical zoom with 16X digital zoom for 288X total zoom capability
- 220 presets with up to 3 selectable group tours (up to 16 individual presets)
- 🛸 Variable speed pan and tilt motors (280°/sec max)

TRUE 12vDC 492FT. IR SURGE PROTECTION

CREST

Contact your Crest Representative today to learn more about this product!



3706 Alliance Drive | Greensboro, NC 27407 | 1-888-50-CREST | www.crestelectronics.com 602

Product Data: CDPA-18X16-147 AHD IR PTZ Dome Camera

| Model Number | CDPA-18X16-147 |
|-------------------------------|---|
| Product Description | 18X AHD Color PTZ Dome Camera with IR |
| Mechanical Pan Rotation Angle | 360° Endless |
| Pan Speed | 280° / Sec |
| Tilt Rotation Angle | 0~90° (Hardware Autoflip) |
| Tilt Speed | 160° / Sec |
| Functions Presets | 220 Positions |
| Group Tour | 4 Programmable (each one capable of 16 presets) |
| Auto Scan | 2 Programmable Auto Scan |
| Privacy Masking Zones | 24 Privacy Zones |
| Auto Flip | Horizontal 180°, Vertical 90° (On / Off) |
| OSD Menu | Multiple Languages on Screen |
| Communication | RS-485 |
| Protocol | Pelco P / D |
| Alarm | 4 In / 2 Out |
| Electrical Power Consumption | 12vDC / 4A |
| Lightning Protection | Transient Voltage 6000V |
| Construction Dimensions | 9" x 10" Dome; 9" x 7" x 5" Wall Mount |
| Weight | 16 lbs, 8 oz |
| Operating Temperature | -40 ~ 140° F |
| Camera Module Image Sensor | 1/3" Sony 1.4MP CMOS Sensor |
| Number of Effective Pixels | 1280H x 720V (NTSC) |
| Resolution | 720p |
| Lens Optical | 18X Optical Zoom (5.35mm - 96.3mm) |
| Digital | 16X (288X with Optical) |
| Zoom Speed | Quick / Slow |
| Minimum Illumination | 0 Lux with IR |
| Luminance S/N Ratio | 50dB AGC Off |
| BLC | On / Off |
| Freeze | On / Off |
| Iris | Auto / Manual |

Specifications subject to change



3706 Alliance Drive | Greensboro, NC 27407 | 1-888-50-CREST | www.crestelectronics.com