## **CP-9507W** Analog Low Light Box Camera





- New 960H+ technology for unsurpassed picture clarity
- LWDR technology for true low-light performance
- True day/night performance, utilizing a motorized IR cut filter
- 0.0001 lux in b/w mode, 0.01 lux in color mode activation level is user selectable
- SD menu for easy set-up via external controls
- Supports video and DC style auto iris lenses
- Low power consumption
- 12vDC or 24vAC dual voltage
- 🛸 2 1/2" (width) x 2 3/8" (height) x 4 3/8" (length)






Contact your Crest Representative today to learn more about this product!



3706 Alliance Drive | Greensboro, NC 27407 | 1-888-50-CREST | www.crestelectronics.com 407

## Product Data: CP-9507W Analog Low Light Box Camera


Front View



Rear View



Side View



Model Numbe **Product Description** Image Pick-Up Devic Horizontal Resolution **Minimum Illuminatio** S/N Rati Automatic Electronic Shutte Auto Gain Contro Auto White Balanc **Backlight Compensation** Scanning Syster Lens Type Compatibilit Synchronous Syster Video Outpu Power Suppl **Power Consumption** Certificatio

| odel Number   | CP-9507W                                 |
|---------------|--|
| t Description | 960H+ WDR Box Camera                     |
| ck-Up Device  | 1/3" Color Sony Super HAD CCD II         |
| al Resolution | 700 TV Lines (Color); 800 TV Lines (B/W) |
| Illumination  | 0.0001 Lux in B/W; 0.01 Lux in Color     |
| S/N Ratio     | More than 52dB (AGC Off)                 |
| ronic Shutter | NTSC: 1/60 - 1/100,000s; User Selectable |
| Gain Control  | Low / Middle / High / Off                |
| /hite Balance | ATW (2500°K-9500°K) / Manual / AWB       |
| ompensation   | BLC / HSBLC / DWDR / Off                 |
| ning System   | 2:1 Interlace; Single Scan               |
| Compatibility | C or CS Mount / Video or DC Powered AI   |
| nous System   | Internal                                 |
| Video Output  | 1 Vp-p / 75 ohms; BNC Connector          |
| ower Supply   | 12vDC (+/-10%) / 24vAC                   |
| Consumption   | 250mA                                    |
| Certification | CE, FCC, ROHS                            |
| Dimensions    | 2 1/2" W x 2 3/8" H x 4 3/8" L           |

Specifications subject to change



3706 Alliance Drive | Greensboro, NC 27407 | 1-888-50-CREST | www.crestelectronics.com