

# 660 Series 6.0-60mm Vari-Focal Lenses



- Available in manual or auto iris versions
- Steel casing with glass optics
- F-stop: 1.4

 **CREST**  
ELECTRONICS INC  
Video Security Since 1974

# Product Data: 660 Series 6.0-60mm Vari-Focal Lenses

	<b>660 Series</b>
<b>Model Number</b>	660 Series
<b>Light Metering</b>	Continuously Variable Average to Peak Light Metering
<b>Input Impedance</b>	High Impedance
<b>EE Precision</b>	Average Value for 0.7 Vpp Video Signal +/-10%
<b>Input Voltage</b>	8.0V to 16V DC (Fixed)
<b>Maximum Current Used</b>	40mA
<b>Level Adjustment Range</b>	0.5 to 1.0 Vpp
<b>Input Signal</b>	Video Signal or Composite Video Signal
<b>Focal Length</b>	6 - 60mm
<b>F-Stop</b>	1.4
<b>Mount</b>	CS
<b>Back Focal Length</b>	7.6 - 11mm
<b>Angle of View</b>	53.13° - 5.72°
<b>Iris</b>	DC (1.4 - 360)
<b>Group / Element</b>	9G / 12E
<b>Image Format</b>	1/3"
<b>Dimensions</b>	3"L x 1 3/8"W x 1 3/4"H
<b>Stopper Iris</b>	8mm (Dia)
<b>Effective Diameter Front</b>	1 3/8"
<b>Effective Diameter Rear</b>	9mm
<b>Weight</b>	6.1 oz

*Specifications subject to change*

