

CDPA-10X16-145

AHD IR PTZ Dome Camera



720p AHD PTZ with IR and 10X Optical Zoom

- ☞ Analog high definition for 720p resolutions over coax
- ☞ IP66 rated weatherproof housing
- ☞ DWDR technology for great performance in all lighting
- ☞ True day/night performance, utilizing a motorized IR cut filter
- ☞ Built-in surge protection (transient 6000V)
- ☞ 0 lux with IR LEDs on
- ☞ High intensity IR array with smart IR LED control for IR projection up to 164 feet
- ☞ 10X optical zoom with 16X digital zoom for 160X total zoom capability
- ☞ 220 presets with up to 3 selectable group tours (up to 16 individual presets)
- ☞ Variable speed pan and tilt motors (200°/sec max)



Contact your Crest Representative today to learn more about this product!



Product Data: CDPA-10X16-145 AHD IR PTZ Dome Camera

	CDPA-10X16-145
Model Number	CDPA-10X16-145
Product Description	10X AHD Color PTZ Dome Camera with IR
Mechanical Pan Rotation Angle	360° Endless
Pan Speed	200° / Sec
Tilt Rotation Angle	0~93° (Hardware Autoflip)
Tilt Speed	80° / Sec
Functions Presets	220 Positions
Group Tour	3 Programmable (each one capable of 16 presets)
Auto Scan	1 Programmable Auto Scan
Privacy Masking Zones	24 Privacy Zones
Auto Flip	Horizontal 180°, Vertical 93° (On / Off)
OSD Menu	Multiple Languages on Screen
Communication	RS-485
Protocol	Pelco P / D / Auto
Electrical Power Consumption	12vDC / 3A
Lightning Protection	Transient Voltage 6000V
Construction Dimensions	5 1/2" x 6 3/4" Dome; 9" x 4 1/2" x 3" Wall Mount
Weight	7 lbs, 8 oz
Operating Temperature	-40 ~ 140° F
Camera Module Image Sensor	1/3" Sony 1.4MP CMOS Sensor
Number of Effective Pixels	1280H x 720V (NTSC)
Resolution	720p
Lens Optical	10X Optical Zoom (5.13mm - 46.3mm)
Digital	16X (160X with Optical)
Zoom Speed	Quick / Slow
Minimum Illumination	0 Lux with IR
Luminance S/N Ratio	50dB AGC Off
BLC	On / Off
Freeze	On / Off
Iris	Auto / Manual

Specifications subject to change

