

# CDP-1210CE-N

## High Speed Day/Night PTZ IP Dome



- ☞ Vandal resistant aluminum, weatherproof body with polycarbonate lower dome
- ☞ 1/4" Exview HAD CCD for outstanding picture quality
- ☞ 10x optical zoom, with 10x digital for 100x total zoom capability
- ☞ Built-in web server
- ☞ Operates on 12vDC or PoE – user selectable
- ☞ Supports static & dynamic IP addresses
- ☞ 10/100 base T Ethernet connection (RJ-45)
- ☞ Includes analog video output (BNC)
- ☞ Utilizes M-JPEG, MPEG-4 or H.264 (user selectable) for high quality streaming video, up to 720 x 480
- ☞ Adjustable bandwidth throttle, allows camera performance to be tailored to the network's capabilities
- ☞ ONVIF compliant



**Video Security Since 1974**

# Product Data: CDP-1210CE-N Hi Speed Day/Night PTZ IP Dome

Model Number		CDP-1210CE-N (10x Zoom)	
Mechanical	Pan Rotation Angle	360° Endless	
	Pan Speed	0 ~ 360° / Sec.	
	Tilt Rotation Angle	0 ~ 180° (Autoflip On); 0 ~ 90° (Autoflip Off)	
	Tilt Speed	0 ~ 360° / Sec.	
Functions	Presets	127 positions with a 10 character label available for each position with different speed steps	
	Group Tour	Max 8 Programmable Group Tours (each one consisting of up to 20 preset steps)	
	Auto Scan	8 Programmable Auto Scan	
	Privacy Masking Zones	4 Privacy Zones	
	Alarm Actions	Home Activate Preset, Group Scanning or Output Per Alarm Input	
	Auto Flip	On / Off	
	OSD Menu	Multiple Languages On Screen	
	Communication	RS-485	
	Protocol	Pelco P / D / Auto	
Electrical	Power Consumption	12vDC / 1.0 Amp	
	Alarm Input	NC / NO	
Construction	Dimensions	6 1/2" D x 6 1/4" H x 4" Dia Lower Dome	
	Weight	2.2 Lbs	
	Operating Temperature	14°F ~ 122°F (Indoor), 0°F ~ 122°F (Outdoor)	
Camera Module	Image Sensor	1/4" Interline Transfer CCD	
	Number of Effective Pixels (NTSC)	768 H x 494 V, 380K	
	Horizontal Resolution	More than 500 TV Lines Composite Output	
	Lens	Optical	10x Optical Zoom (F1.8, F=3.8 - 38mm)
		Digital	10x (100x with Optical)
	Digital Slow Shutter	On / Off	
	Min. Illumination	0.7 Lux @ F1.8 (50IRE) Color; 0.02 Lux B/W	
	Luminance S/N Ratio	50dB AGC Off	
	BLC	Low / Middle / High / Off	
	Flickerless Mode	On / Off Selectable	
	White Balance	Auto / Manual	
Network	Hardware	32 Bit RISC Processor	
	Operating System	Embedded Linux	
	Flash Memory	8 MB	
	Protocol	TCP/IP, DDNS	
	Interface	10/100 Base T Ethernet (RJ-45)	
	Compression	Selectable M-JPEG & MPEG-4, H.264	
	Resolutions	320x240, 720x480	
	Frame Rate	30 FPS (720x480)	

Specifications subject to change



**Video Security Since 1974**