

CJ-27CS


1/3" Color Hi-Res Indoor Dome Camera



- 420 lines of resolution
- 0.3 lux with f1.2 lens
- Vari-focal 4-9mm auto iris lens
- Automatic back light compensation, AGC, AWC
- Hi-speed auto electronic shutter – up to 1/100,000
- Aesthetic polycarbonate construction
- Compact size – 5" dia x 3 5/8" h

 **CREST**
ELECTRONICS INC
Video Security Since 1974

Product Data: CJ-27CS 1/3" Color Hi-Res Indoor Dome Camera



Model Number	CJ-27CS
Image Pick-Up Device	1/3" CCD Sony Super HAD
Effective Picture Elements	NTSC: 768x494 (HxV)
Horizontal Resolution	420 TV Lines
Minimum Illumination	0.3 Lux @ F1.2
S/N Ratio	More than 48dB
Auto Electronic Shutter	NTSC: 1/60-1/100,000s, Automatic
Auto Iris Control	DC Drive Iris Control
Gamma Characteristic	0.45
Lens Furnished	4-9mm (DCAI)
Focal Length/Aperture Ratio	f=4-9mm / F1.2-360
Angle Field of View	Wide=78.2°x57.6°; Tele=37.2°x26.8°
Auto Gain Control	Automatic
Auto White Balance	Automatic
Back Light Compensation	Automatic
Scanning System	Interlace 2:1
Synchronous System	Internal, negative sync
Video Output	1 Vp-p / 75 ohms
Power Supply	12vDC
Power Consumption	100mA max
Operating Temperature	14 ~ 122°F
Dimensions	5" dia x 3 5/8" h

Model Number	CJ-27CS
Image Pick-Up Device	1/3" CCD Sony Super HAD
Effective Picture Elements	NTSC: 768x494 (HxV)
Horizontal Resolution	420 TV Lines
Minimum Illumination	0.3 Lux @ F1.2
S/N Ratio	More than 48dB
Auto Electronic Shutter	NTSC: 1/60-1/100,000s, Automatic
Auto Iris Control	DC Drive Iris Control
Gamma Characteristic	0.45
Lens Furnished	4-9mm (DCAI)
Focal Length/Aperture Ratio	f=4-9mm / F1.2-360
Angle Field of View	Wide=78.2°x57.6°; Tele=37.2°x26.8°
Auto Gain Control	Automatic
Auto White Balance	Automatic
Back Light Compensation	Automatic
Scanning System	Interlace 2:1
Synchronous System	Internal, negative sync
Video Output	1 Vp-p / 75 ohms
Power Supply	12vDC
Power Consumption	100mA max
Operating Temperature	14 ~ 122°F
Dimensions	5" dia x 3 5/8" h

Specifications subject to change

