

CP-47HS-N Hi-Def WDR Indoor Dome



- Utilizes state-of-the-art video compression engine – allows real time streaming of true 720p high definition video
- Triple codec – allows simultaneous streaming of three independent video streams, including H.264, MPEG4 and MJPEG, all with individual settings and requirements
- Operates with IPv4, IPv6 and DDNS protocols
- Vari-focal 2.8-10mm auto iris lens
- Operates on 12vDC or PoE – auto selectable
- Digital image stabilization
- Includes easy-to-use installation software with auto detect feature
- Lightweight plastic construction for easy mounting



**CREST**
ELECTRONICS INC
Video Security Since 1974

Product Data: CP-47HS-N Hi-Def WDR Indoor Dome

Model Number	CP-47HS-N
Product Description	Hi-Def WDR Indoor Dome
	CAMERA
Pick-Up Elements	1/3" 1.3 Progressive CMOS
Resolution	720p
Minimum Illumination	0.5 Lux Color; 0.1 Lux B/W
Lens	2.8 ~ 10mm Vari-Focal Auto Iris
Auto Iris	DC Drive
White Balance	ATW / AWC
WDR Level	Up to x128, User Selectable
Gain Control	Automatic
Motorized IR Cut Filter	On/Off/Auto Selectable
Analog Video Output	BNC
Operating Temperature	14°F ~ 131°F
Power Source	12vDC, 800ma, or PoE, Selectable
Dimensions	4 3/4"Dia x 4"H
Housing	Plastic Body, Polycarbonate Lower Dome
	NETWORK
Hardware	32 Bit RISC Processor
Operating System	Embedded Linux
Flash Memory	5 DHC Memory Card
Protocol	TCP/IP, DDNS
Interface	10/100 Base T Ethernet (RJ-45)
Compression	H.264, MPEG-4 or M-JPEG
Resolutions	CIF, D1, 720p
Frame Rate	30 FPS (720p)

Specifications subject to change

