

CP-48MS

True Day/Night Color Enviro Vandal Dome




- True day/night performance, utilizing a motorized IR cut filter
- All camera parameters are user selectable, utilizing an easy-to-navigate OSD via external keypad (included)
- 550 lines of resolution
- 0.008 lux in b/w mode, 0.02 lux in color – mode activation level user selectable
- 4-9mm auto iris vari-focal lens
- Low power consumption (180ma)
- Vandal proof and water proof housing (IP66)
- Internal service monitor connection
- Recessed or surface mount
- Compact size – only 5 3/4" dia x 3 7/8" h



Video Security Since 1974

Product Data: CP-48MS True Day/Night Color Enviro Vandal Dome



Model Number
Image Pick-Up Device
Effective Picture Elements
Horizontal Resolution
Minimum Illumination
S/N Ratio
Auto Electronic Shutter
Auto Iris Control
Flickerless Mode
Gamma Characteristic
Lens Furnished
Focal Length/Aperture Ratio
Angle Field of View
Auto Gain Control
Auto White Balance
Back Light Compensation
Scanning System
Synchronous System
Video Output
Power Supply
Power Consumption
Operating Temperature
Dimensions

CP-48MS
1/3" CCD Sony Super HAD
NTSC: 768x494 (HxV)
550 TV Lines
0.008 Lux @ F1.2
More than 48dB (AGC Off)
NTSC: 1/60-1/100,000s, ON/OFF Switchable
DC Drive Iris Control
NTSC: 1/100s, ON/OFF Switchable
0.45
4-9mm DCAI
f=4~9mm / F1.2~360
4~9mm = Wide=82.2°x62°; Tele=28.6°x21.5°
User Selectable
User Selectable
User Selectable
Interlace 2:1
Internal, negative sync
1 Vp-p / 75 ohms
DC 12v / AC 24v dual voltage
DC 12v, 50/60Hz, 180mA; AC 24v, 50/60Hz, 4.0w
14 ~ 122°F
5 3/4" dia x 3 7/8" h

Specifications subject to change

 **CREST**
ELECTRONICS INC
Video Security Since 1974